
LogTag Recorders



Product Highlights


- A real time clock provides date/time stamps for each temperature reading.
- Push-to-start button with optional delay or a specific time & date.
- Comprehensive customisation options including alert settings, sample interval and trip duration.
- Robust and durable polycarbonate case with lug for secure mounting.
- Up to 8,000 recordings enough for the longest trip
- In-transit inspections can be recorded at the push of a button.
- Industry best download time less than 5 seconds for fully memory.




TREX-8 Specifications


Product Model	TREX-8
Measurement Range	-40°C ~ +85°C (-40°F ~ +185°F)
Capacity	8032 readings (16K bytes memory)
Sampling Interval	Adjustable, 30 sec to several hours
Environmental	IP65 (roughly equivalent to NEMA 4)
Power Source	3V LiMg battery
Battery Life	2 ~ 3 years of normal use (based on 15 minute logging, download data monthly.
01	
Size	86mm(H)x54.5mm(W)x8.6mm(T)
Weight	86mm(H)x54.5mm(W)x8.6mm(T) 35g

Accuracy/Resolution Charts





Recommended Applications





FDA CFR21 Part 11 Compliance





RoHS Directive





EMC Compliance

Our FREE LogTag Analyzer software provides an easy to use, powerful platform for configuring any LogTag recorder product before deployment and for data download & analysis when the recorder is retrieved.

Accessories



ST100 Remote Temperature Probes



Protective Enclosure



Wall Mount Bracket