LogTag Recorders

TRIX-8 Multi-Use Temperature Recorder

The LogTag[®] TRIX-8 is a versatile, wide range, multi-trip Temperature Recorder, featuring high resolution temperature readings over a measurement range of -40°C to +85°C (-40°F to +185°F).


Enclosed in a robust and durable polycarbonate case - the TRIX-8 is equipped with a unique external temperature sensor arrangement providing fast reaction time to temperature change and a real time clock which provides date/time stamps for each temperature reading.

Product Highlights

TEMPERATURE RECORDER

ALERT


- A real time clock provides date/time stamps for each temperature reading.
- Push-to-start button with optional delay or a specific time & date.
- Comprehensive customisation options including alert settings, sample interval and trip duration.
- Robust and durable polycarbonate case with lug for secure mounting.
- Up to 8,000 recordings enough for the longest trip.
- In-transit inspections can be recorded at the push of a button.
- Complies with industry standards including EN12830.
 WHO PQS Pre-qualified under E06 devices: PQS
 Code E06/06
- Industry best download time less than 5 seconds for fully memory.




TRIX-8 Specifications


Product Model	TRIX-8
Measurement Range	-40°C ~ +85°C (-40°F ~ +185°F)
Capacity	8032 readings (16K bytes memory)
Sampling Interval	Adjustable, 30 sec to several hours
Environmental	IP65 (roughly equivalent to NEMA 4)
Power Source	3V LiMg battery
Battery Life	2 ~ 3 years of normal use (based on 15 minute logging, download data monthly.
Size	86mm(H)x54.5mm(W)x8.6mm(T)
Weight	35g
Case Material	Polycarbonate
Alarm Functions	High/low, single events & cumulative supported, 'OK'/'ALERT' LEDs

Accuracy/Resolution Charts





Recommended Applications









21CFRPart1



WHO PQS Prequalified



Our FREE LogTag Analyzer software provides an easy to use, powerful platform for configuring any LogTag recorder product before deployment and for data download & analysis when the recorder is retrieved.





LogTag's unique interface cradle design provides rapid & reliable LogTag data transfer.

Note: Users do not need to purchase more than one Interface Cradle per LogTag product.

Accessories



Protective Enclosure



Wall Mount Bracket

LogTag Recorders