LogTag Recorders

USRIC-8 USB PDF Temperature Recorder

Designed as a single-use, cost effective & reliable temperature recorder, the LogTag[®] USRIC-8 measures and stores real time temperature readings over a measurement range of -25°C to +60°C (-13°F to +140°F).

Enclosed in a robust and durable polycarbonate case, the USRIC-8 plugs directly into the computer USB to automatically generate a fully detailed PDF report with the option to download the data using the freely available LogTag® Analyzer software for a more detailed analysis.

Product Highlights

LogTag

USB PDF TEMPERATURE RECORDER


ALERT

STOP

START

S/N:4035001006


- Integral USB connector no separate Interface • Cradle required.
- Automatically generates a PDF report no • special software required.
- Automatically generates an encrypted LogTag • data file - for a more detailed analysis.
- Fully user configurable via LogTag Analyzer for individual alarm settings, start options, trip length and log interval. No need to buy a special recorder for each trip.
- Robust and durable polycarbonate case with lug • for secure mounting.
- Up to 8,000 recordings enough for the longest • trip.
- In-transit inspections can be recorded at the push of a button.
- Suitable for multiple independent receivers, • clinical trials and last-mile distribution.




USRIC-8 Specifications

Product Model	USRIC-8
Measurement Range	-25°C ~ +60°C (-13°F ~ +140°F)
Capacity	8,001 real time temperature recordings, non-volatile memory
Sampling Interval	Configurable from 1 minute to 18 hours
Start Options	Push button start or specific date/time
Start up delay	Configurable 0 seconds to 45 days
Environmental	IEC 60529: IP64 with USB cap fitted
Power Source	3V Lithium battery- non replaceable
Battery Life	Shelf life of up to two years before configuration. Six months operating life from the time of configuration.
Size	93mm(H) x 54.5mm (W) x 8.6mm (T) including USB cap
Weight	32g
Case Material	Polycarbonate
Alarm Functions	High/low, single, consecutive and cumulative alarm events, 'OK'/'ALERT' indicators
Connection Interface	USB 2.0, A-type plug
Software	Adobe Reader, LogTag Analyzer [®] 2.5 or higher

Accuracy/Resolution Charts





Recommended Applications











Our FREE LogTag Analyzer software provides an easy to use, powerful platform for configuring any LogTag recorder product before deployment and for data download & analysis when the recorder is retrieved.

Accessories



Protective Enclosure



Wall Mount Bracket

Page 2 of 2